| Γ | 1 | | | 2 | | | 4 | 5 | Customer drawing | |
|---|-----|----------------------|---------------|----------|------------|-------|------|-------|------------------|--|
| | REV | V ECN NO DESCRIPTION | | DATE | APPROVED | | | | | |
| | AA | AA – NEW RELEASED | | | 2015.06.18 | CLARA | | | | |
| | | | | | | | | | | |
| A | | | | | | | | | Α | |
| | | | | | | | | | | |
| | | | | | | | 10.1 | 414 5 | | |
| | | | ALL | N GTALER | | | 16.1 | ¢14.5 | | |
| | | | | | | | 6.2 | | | |
| | | | Form | nat D.C | | Т | | | | |
| | | | 1219 | BILLER | | TX I | | | | |
| | | | WW.B | omean.ee | | M12x1 | 68 + | | 4 | |
| | | | | | | | | | | |
| E | | | | | | | | | В | |
| | | | | | | | | | | |
| | | | | | | | | | 60 | |
| | | | Dimensions"A" | Used for | | | | | | |

3

| | For | receptacle | connectors |
|--|-----|------------|------------|
|--|-----|------------|------------|

0.8

Ð

1

С

| DO | BOMCAN | | | | J This drawing contains information that is proprietary to BOMCAN and should not be used without written permission. Powered by bomcan.com | | | | |
|-----------------------|--|--------------|----------|------------------|--|-------|------------------------|--|--|
| DESCRIPTION | M12x1 THREAD CONNECTOR ACCESSORIES PROTECTION DUST CAP | | | | | | | | |
| DWG NO | DWG NO CAP-M1202 | | | BOMCAN PART No - | | | j | | |
| DRAWN BY CLARA 2015.0 | | CUSTOMER P/N | | - | | | | | |
| CHECKED BY | CALEB 2015.06.18 | | SIZE: A4 | SHEET | UNIT | SCALE | Third angle projection | | |
| APPROVED BY | BILL 2015.06.18 | | REV: AA | l of l | MM | FREE | | | |
| | 4 | | | 5 | | | A4 | | |

Material specifications: 1. Shell:

OD=3mm

OD=11.5mm

OD=13mm

OD=15mm

С

www.bomcan.com

1

1. Shell:PA,Black2. O-ring:Rubber,Black3. Flexibility ribbon:PU,Black

2

Square Socket

PG9 & M16

M12x1

Cable