


1	2	3	4	5
REV	ECN NO	DESCRIPTION	DATE	APPROVED
AA	-	NEW RELEASED	2017.03.15	CLARA




Electrical specifications:
 Use of voltage range: 5V
 Current range: 2A
 Temperature range: -20°C~+80°C

Material specifications
 Cable: Type-C Cable
 Connector: Type-C Connector
 Overmolding: Black PVC

Mechanical properties
 Minimum bending radius: Fixed installation: 8x Cable OD
 Flexible installation: 10x Cable OD

Electrical testing of finished cable
 100% Open / Short / Miswiring testing
 Insulation resistance: DC300V 10MΩ
 Conductor resistance: 5Ω

Manufacturer: Bomcan



www.bomcan.com



This drawing contains information that is proprietary to BOMCAN and should not be used without written permission. Powered by bomcan.com

DESCRIPTION	USB4 TYPE C CABLE ASSEMBLY SCREW LOCKING FIXED			
DWG NO	-	BOMCAN PART No	USB4-SCREW	
DRAWN BY	CLARA 2017-03-15	CUSTOMER P/N	-	
CHECKED BY	CALEB 2017-03-15	SIZE: A4	SHEET	UNIT
APPROVED BY	BILL 2017-03-15	REV: AA	1 of 1	MM
			SCALE	Third angle projection
			FREE	